

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) A method for manufacturing a medical device, comprising the steps of:

providing a core member having a proximal region and a distal region;

disposing a polymer jacket over the distal region of the core member, the polymer jacket having a substantially smooth outer surface;

winding a coil over the polymer jacket, wherein the coil is wound under tension over the polymer jacket; and

heating the polymer jacket so that the coil moves inward into the polymer jacket, relieving the coil tension and wicking a portion of the polymer jacket ~~tension is relieved and the outer surface of the jacket wicks~~ between adjacent windings of the coil, providing an outer surface of the polymer jacket relative to the coil in the final medical device that has desirable flexibility characteristics.

2. (original) The method of claim 1, wherein the polymer jacket includes a thermoplastic material and wherein the step of disposing the polymer jacket over the distal region of the core member includes disposing a thermoplastic polymer jacket over the distal region of the core member.

3. (currently amended) A method for manufacturing a medical device, comprising the steps of:

providing a core member having a proximal region and a distal region;

disposing a polymer jacket over the distal region of the core member, the polymer jacket having a substantially smooth outer surface;

winding a coil over the polymer jacket, wherein the coil is wound under tension over the polymer jacket;

heating the polymer jacket so that the coil tension is relieved and the outer surface of the polymer jacket wicks between adjacent windings of the coil, providing an outer surface of the polymer jacket relative to the coil in the final medical device that has desirable flexibility characteristics; and

wherein the coil includes a fluorocarbon material and wherein the step of winding a coil over the polymer jacket includes winding ~~[[a]]~~ the coil that includes a fluorocarbon material over the polymer jacket.

4. (currently amended) A method for manufacturing a medical device, comprising the steps of:

providing a core member having a proximal region and a distal region;

disposing a polymer jacket over the distal region of the core member, the polymer jacket having a substantially smooth outer surface;

winding a coil over the polymer jacket, wherein the coil is wound under tension over the polymer jacket;

heating the polymer jacket so that the coil tension is relieved and the outer surface of the polymer jacket wicks between adjacent windings of the coil, providing an outer surface of the polymer jacket relative to the coil in the final medical device that has desirable flexibility characteristics; and

wherein the coil ~~include~~ includes a central core material and an outer coating surrounding the central core material, and wherein the step of winding a coil over the polymer jacket includes winding ~~[[a]]~~ the coil that includes a central core material and an outer coating surrounding the central core material over the polymer jacket.

5. (original) The method of claim 4, wherein the outer coating includes a fluorocarbon material.

6. (currently amended) The method of claim 1, wherein the step of heating the jacket so that the coil moves inward into the polymer jacket, relieving the coil tension and wicking a

~~portion of the polymer jacket tension is relieved and the outer surface of the jacket wicks~~
between adjacent windings of the coil includes embedding the coil within the jacket.

7. (currently amended) A method for manufacturing a guidewire, comprising the steps of:

providing a core member having a proximal region and a distal region;
disposing a jacket having an outer surface over the distal region of the core member;
disposing a coil over the outer surface of the jacket; and
embedding the coil ~~within~~ into the outer surface of the jacket in a manner that alters the shape of the outer surface of the jacket so that the outer surface of the jacket wicks outward between adjacent windings of the coil, providing an outer surface of the jacket relative to the coil in the final guidewire that has desirable flexibility characteristics.

8. (currently amended) A method for manufacturing a guidewire, comprising the steps of:

providing a core member having a proximal region and a distal region;
disposing a jacket having an outer surface over the distal region of the core member;
disposing a coil over the outer surface of the jacket;
embedding the coil ~~within~~ into the outer surface of the jacket in a manner that alters the shape of the outer surface of the jacket so that the outer surface of the jacket wicks outward between adjacent windings of the coil, providing an outer surface of the jacket relative to the coil in the final guidewire that has desirable flexibility characteristics; and

wherein the step of disposing a coil over the jacket includes winding ~~[[a]]~~ the coil under tension about the outer surface of the jacket.

9. (currently amended) A method for manufacturing a guidewire, comprising the steps of:

providing a core member having a proximal region and a distal region;
disposing a jacket having an outer surface over the distal region of the core member;
disposing a coil over the outer surface of the jacket;

embedding the coil ~~within~~ into the outer surface of the jacket in a manner that alters the shape of the outer surface of the jacket so that the outer surface of the jacket wicks outward between adjacent windings of the coil, providing an outer surface of the jacket relative to the coil in the final guidewire that has desirable flexibility characteristics;

wherein the step of disposing a coil over the jacket includes winding ~~[[a]]~~ the coil under tension about the outer surface of the jacket; and

wherein the step of embedding the coil within the jacket includes relieving the tension within the coil.

10. (currently amended) The method of claim 7, wherein the step of disposing a coil over the outer surface of the jacket includes disposing the coil over a proximal section of the jacket.

11. (original) The method of claim 10, further comprising the step of disposing a covering over a distal section of the jacket.

12. (original) The method of claim 7, further comprising the step of disposing a covering over the coil.

13-20. (cancelled)

21. (currently amended) A method for manufacturing a guidewire, comprising the steps of:

providing a core member having a proximal region and a distal region;

disposing a thermoplastic jacket having an outer surface over the distal region of the core member;

disposing a coil under tension about the outer surface of the jacket, the coil including a fluorocarbon material; and

heating the thermoplastic jacket so that tension of the coil is relieved and the coil embeds within the jacket.

22. (currently amended) A method for manufacturing a guidewire, comprising the steps of:

providing a core member having a proximal region and a distal region;

disposing a thermoplastic jacket having an outer surface over the distal region of the core member, the jacket having a proximal section and a distal section;

disposing a coil under tension about the proximal section of the jacket, the coil including a fluorocarbon material;

heating the thermoplastic jacket so that tension of the coil is relieved and the coil embeds within the jacket; and

disposing a coating over the distal section of the jacket.

23. (cancelled)

24. (new) The method of claim 3, wherein the coil moves inward into the polymer jacket, thereby altering the shape of the outer surface of the polymer jacket.

25. (new) The method of claim 4, wherein the coil moves inward into the polymer jacket, thereby altering the shape of the outer surface of the polymer jacket.

26. (new) The method of claim 7, wherein the step of disposing the coil over the outer surface of the jacket includes winding the coil under tension about the outer surface of the jacket; and

wherein during the step of embedding the coil into the outer surface of the jacket, the coil moves radially inward into the jacket, relieving the coil tension and wicking a portion of the jacket outward between adjacent windings of the coil.

27. (new) The method of claim 7, wherein the coil includes a central core material and an outer coating surrounding the central core material.

28. (new) The method of claim 8, wherein the coil includes a central core material and an outer coating surrounding the central core material.

29. (new) The method of claim 9, wherein the coil includes a central core material and an outer coating surrounding the central core material.

30. (new) The method of claim 21, wherein during the step of heating the thermoplastic jacket, the coil moves inward into the thermoplastic jacket, altering the shape of the outer surface of the thermoplastic jacket.

31. (new) The method of claim 22, wherein during the step of heating the thermoplastic jacket, the coil moves inward into the thermoplastic jacket, altering the shape of the outer surface of the thermoplastic jacket.